

DOMESTIC ONE-PIECE TANKS



Full specifications
available from KMG Ltd.
on request.

Fibreglass insulated F30, one-piece water tanks, ranging from 45 to 2,730 litre (10 to 600 gallons) nominal. Helping to meet your Health & Safety requirements.

KMG Ltd. has been at the forefront of the Water Storage Industry, since 1973, specialising in the design and manufacture of fibreglass one-piece water storage tanks, lids, condensation trays and fibreglass insulated F30 one-piece water storage tanks. Non-standard sizes are also available, to customer specifications.



DOMESTIC ONEPIECE TANKS SPECIFICATIONS

Many Local Authorities, Consultants, Engineers & Contractors specify and use our Fibreglass insulated F30 tanks, secure in the knowledge that both they and their clients are in safe hands, and helping them meet their Health & Safety obligations.

In order to comply with Health & Safety Directives, (which state that water, that may be consumed by humans, must be held in Insulated tanks, and that all tanks must meet the following criteria),

- **Fibreglass one-piece watertanks**
- **Water must be of potable quality (drinkable)**
- **Lids must be sealed and insulated**
- **Tanks must have screened air inlet and screened overflow**
- **Tanks must be insulated, as this reduces the likelihood of freezing in winter and assists in keeping the water temperature low in summer time**

Model	Length	Width	Height	Height Insulated F30	Litres nominal	Gallons nominal
KP10	495	370	345	420	45	10
KP25	1200	530	340	420	114	25
KP40 lg	1041	546	457	457	182	40
KP40 sq	670	530	565	640	182	40
KP50	1216	545	457	545	227	50
KP70	1230	575	584	650	318	70
KP100	1310	680	610	685	454	100
KP150	1645	1075	545	610	682	150
KP200	1660	1055	690	765	909	200
KP250	1660	1055	845	920	1136	250
KP300	1660	1245	845	1015	1363	300
KP400	2545	1330	615	775	1818	400
KP500	1880	1375	1140	1300	2275	500

Round Tank	Diameter	Height	Height if Insulated	Litres nominal	Gallons nominal
KP600	1830	1240	1340	2730	600

Please note: Insulation slows down, but does not prevent heat loss or heat gain, over protracted periods.

Additional information is available in BS 7491 & BS 6700.

Head Office: Killarney Manufacturing Group, Ballyspillane Ind Estate, Killarney, Co Kerry, Ireland

Ireland Tel + 353 64 32421 • UK Tel + 44 1453 791616

Email: info@kmggroup.eu • Web: www.kmggroup.eu



In accordance with Killarney Manufacturing Group's normal policy of product development this specification is subject to change without notice.